

STANDARD

STYLE 3522

HIGH PERFORMANCE
 22-oz. FABRIC
 Typical Properties

Base Fabric Type	Polyester
Base Fabric Weight (nominal)	6.0 oz/yd ²
Finished Coated Weight	22 oz/yd ²
ASTM D751	+2/-1 oz/yd ²
Tongue Tear	8" x 10" sample @ 12"/minute
ASTM D751	150/150 lb _f
Grab Tensile	450/450 lb _f
ASTM D751	
Strip Tensile	325/300 lb _f /in
ASTM D751 Procedure B	
Adhesion	10 lb _f /in
ASTM D751 RF Weld	
Hydrostatic Resistance	500 psi
ASTM D751 Procedure A	
Low Temperature	1/8 in mandrel, 4 hr
ASTM D2136	LTC: Pass @ -40° F LTA: Pass @ -67° F
Flame Resistance	Sample not consumed
FMVSS 302	Pass 4 in/min.
Roll Specifics	Width up to 75 in. Length 110 yd.

Unless stated otherwise, values presented above represent the minimum expected measurements at the time of manufacture. We believe this information is the best currently available on the subject. We offer it as a suggestion in any appropriate experimentation you may care to undertake. It is subject to revision as additional knowledge and experience are gained. We make no guarantee of results and assume no obligation or liability whatsoever in connection with this information.

Issued November 2006